



MATERIALS:

100% Aluminum, fire resistant.

FINISH:

Natural aluminum, comes compressed in a plastic bag with printed installation instructions.

SPF

DESCRIPTION:

Aluminum flexible duct, extends up to 8FT. Available in diameters since 4" up to 16" in 2" intervals.

INSTRUCTIONS FOR THE INSTALLATION OF DUCT

- 1.- Determine the length of the product you need. Allow extra length for elbows and joints.
- 2.- Remove the pipeline, fully extend, measure and mark the desired length.
- 3.- With sheet metal scissors cut the duct.

TO CONNECT THE CONDUIT TO A NECK, TO A PLUG OR A CASH REGISTER

- 1.- Slide the duct over the metal mounting a minimum of two inches.
- 2.- Ensure the assembly of metal duct with four (4) wraps of tape, half and half in the duct in the neck.
- 3.- Install the folded material about an inch from the end of the neck.

NOTE:

- The excessive product should be removed.
- In the pipeline changes direction, the dimension between the center of the duct and the center of the curve should not be less than the diameter of the pipeline.
- An inadequate support can result in reduced air output.

AIR DISTRIBUTION PRODUCTS

SPIRO DUCT + FITTINGS + GRILLES + DIFFUSERS + FILTERS + FLEXIBLE DUCT + ACCESSORIES

Verbet reserve the right of making any change without any prior notice.